

Single Phase Pad Mounted Distribution Transformers

Product Range and Equipment Options

Types Offered	Type 1	Type 2	TrimLine	MicroTrim
kVA Ratings	5 - 333	5 - 333	5-50	5-25
High Voltage	2.4 - 19.9 kV	2.4-19.9 kV	2.4 - 14.4 kV	2.4 - 14.4 kV
BIL	150 kV (max)	150 kV (max)	125 kV (max)	125 kV (max)
Low Voltage	600 v (max)	600 v (max)	600 v (max)	600 v (max)

Optional Equipment

	Type 1	Type 2	TrimLine	MicroTrim
H.V. Taps	X	X	X	X
Dual Voltage	X	X	X	2.1 Ratio Only
Internal Expulsion Fuse Link	X	X	X	X
Bay-o-Net Expulsion Fuse	X	X	X	X
Full Range CL Fuse (Dry Well)	X	X	-	-
Partial Range CL Fuse (Internal)	X	X	X	X
Secondary Circuit Breaker	X	X	X	X
Under Oil MOV Arrester	X	X	X	X
On-Off High Voltage Switch	X	X	-	-
4 Position High Voltage Switch	X	X	-	-
Removable Stud Bushing Wells	X	X	X	X
Load Break Bushing Inserts	X	X	X	X
Integral Load Break Bushings	X	X	X	X
L.V. Insulated Stud Bushings	X	X	X	X
L.V. Bushing Spade Terminals	X	X	X	X
L.V. Cable Lead Bushing	-	-	-	X
Poly Pad	-	-	X	X